



DUBLIN - Interactive Touch Screen Kiosk

Let your visitors know exactly what they want to know, where they are and where they need to go

Main features

- Projected capacitive (PCAP) 10-point multi-touch
- Single or Dual Sided Screen option
- Free-standing design with option to bolt down base plate
- Power & data feed from rear panel or floor through the base plate
- Key lockable access service door
- Ergonomic and compact structure
- User friendly, easy for maintenance



Touch technology - Capacitive

The Projective Capacitive (PCAP) touch technology with 12 touch points ensures a seamless and accurate touch response. With its AMVA3 LED panel, it offers exceptional colour performance, high contrast and wide viewing angles.

This technology uses a sensor-grid of micro-fine wires integrated into the glass that covers the screen. Touch is detected because electrical characteristics of the sensor grid change when human finger is placed on the glass. Thanks to the glass overlay this technology is highly durable, and the touch function remains unaffected even if the glass is scratched.

It offers perfect picture performance and will work with human finger (also latex gloved) and stylus-pen.



Smart Design

The sleek look is achieved with a striking aluminium surround and edge-to-edge vandal proof tempered glass front panel



Plug and Play

If there is no internet access available the screen can still be updated thanks to their backup USB update option.



24/7 Commercial Use

A commercial grade panel, with a lifespan of 50.000 hours and high quality compenets ensure that this display can be in constant use 24/7.



Screen Size	32"	43"	49"	55"
Model Number	T32TR-T	T43TR-T	T49TR-T	T55TR-T

Technical Specifications

Screen

Screen Size	32" 43" 49" 55"
Resolution	32" 1920x1080 - 43" 49" 55" 4K
Brightness	450 cd/m2
Aspect Ratio	16:9
Contrast Ratio	5000:1
Viewing Angle	178:178
Response Time	8ms

Touch

Touch Technology	PCAP - Projected Capacitive
Touch Points	Multi Touch
Response Time	8 ms
OS	Windows, Linux
Protection Glass	Tempered Anti Glare
Touch interface	USB
Touch method	finger, stylus, glove (latex)

Other

Application	Indoor
Colour	RAL 7047 Grey (optional)
Installation	Floor bolting / Free Standing
Enclosure	Metal
Working temperature	0°C~50°C
Power supply	AC 100-240V 50/60HZ



Dimension (mm)

Size	Model Name	A	B	C	D	E	F
32"	T32TR-T	1750	595	694	495	80	300
43"	T43TR-T	1828	725	940	625	81	300
49"	T49TR-T	1950	810	1072	700	80	300
55"	T55TR-T	2097	880	1205	780	80	300



Bravour Deutschland GmbH
 Alt-Heerdt 104
 40549 Düsseldorf - Germany
 Phone: (+49) 322 21093
 E-mail: info@bravour.com

Bravour Nederland BV
 De Rijn 7c
 5684 PJ Best - The Netherlands
 Phone: +31 (0) 40 2988 980
 E-mail: info@bravour.com

Bravour France SAS
 23, Rue de Richelieu
 75001 Paris - France
 Phone: +33 (0) 1 82 88 06 52
 E-mail: info@bravour.com