




**VILNIUS - Interactive Touch Screen Kiosk**

# Interact with technology in new ways.


## Main features

- Free-standing design with option to bolt down base plate
- Power & data feed from rear panel or floor through the base plate
- Vertical orientation
- Key lockable access service door
- Ergonomic and compact structure
- Option of colour




### Touch technology - Capacitive

The Projective Capacitive (PCAP) touch technology with 12 touch points ensures a seamless and accurate touch response. With its AMVA3 LED panel, it offers exceptional colour performance, high contrast and wide viewing angles. This technology uses a sensor-grid of micro-fine wires integrated into the glass that covers the screen. Touch is detected because electrical characteristics of the sensor grid change when human finger is placed on the glass. Thanks to the glass overlay this technology is highly durable, and the touch function remains unaffected even if the glass is scratched.




### Smart Design

The sleek look is achieved with a striking aluminium surround and edge-to-edge vandal proof tempered glass front panel



### Plug and Play

If there is no internet access available the screen can still be updated thanks to their backup USB update option.



### 24/7 Commercial Use

A commercial grade panel, with a lifespan of 50.000 hours and high quality components ensure that this display can be in constant use 24/7.




## Technical Specifications

Screen	
Screen Size	27" or 32"
Screen Orientation	Vertical
Resolution	1920x1080
Brightness	27" 300 cd/m2   32" 450 cd/m2
Aspect Ratio	16:9
Viewing Angle	178:178
Response Time	8ms

Touch	
Touch Technology	PCAP - Projected Capacitive
Touch Points	Multi Touch
Response Time	8 ms
OS	Windows, Linux
Protection Glass	Tempered Anti Glare
Touch interface	USB
Touch method	finger

Other	
Application	indoor
Colour	Red
Installation	Floor bolting / Free Standing
Enclosure	Metal
Working temperature	0°C~50°C
Power supply	AC 100-240V 50/60HZ



Dimension (mm)

Size	Model Name	A	B	C	D	E
27"	K27FV	1700	555	610	121	500
32"	K32FV	1700	595	650	122	540



**Bravour Deutschland GmbH**  
 Alt-Heerdt 104  
 40549 Düsseldorf - Germany  
 Phone: (+49) 322 21093  
 E-mail: [info@bravour.com](mailto:info@bravour.com)

**Bravour Nederland BV**  
 De Rijn 7c  
 5684 PJ Best - The Netherlands  
 Phone: +31 (0) 40 2988 980  
 E-mail: [info@bravour.com](mailto:info@bravour.com)

**Bravour France SAS**  
 23, Rue de Richelieu  
 75001 Paris - France  
 Phone: +33 (0) 1 82 88 06 52  
 E-mail: [info@bravour.com](mailto:info@bravour.com)