

## ST-300W Specifications



### ST-300W-CT Timer Controller & Transmitter

Screen Size	7"
Active Display Area	164.90mm(L)×100.00mm(W) 6.5" x 3.94"
Resolution	800×480 pixel
Touch type	Capacitive
Time Adjustment	Adjustable timer settings
Connection	Wired & Wireless
Mode Settings	Remote / Local
Local Or Remote Mode Selection	Adjustable via 5" Podium Display
Screen ID	Selectable screen ID up to 20
Remaining Time	Display
Time Status	Color status indication (Green/Yellow/Red)
Warning Message	Blink
Brightness	300 cd/m2
Color	65K 65536 colors
Backlight	LED
Power supply	DC 5V 2A

### ST-300W-MC Stage Display

Screen Size	10"
Active Display Area	222.72mm(L)×125.28mm(W)
Resolution	1024×600 pixel
Touch type	Capacitive
Connection	Wired & Wireless
Mode Settings	Remote / Local
Local Or Remote Mode Selection	Adjustable via 5" Podium Display
Brightness	300 cd/m2
Color	65K 65536 colors
Backlight	LED
Power supply	DC 5V 2A

### ST-300W-RD Podium Display

Screen Size	5"
Active Display Area	120.7mm(L)×75.8mm(W) - 4.75" x 3"
Resolution	800×480 pixel
Touch type	Capacitive

Connection	Wired & Wireless
Mode Settings	Remote / Local
Local Or Remote Mode Selection	Adjustable via 5" Podium Display
Settings Password	1234
Brightness	300 cd/m2
Color	65K 65536 colors
Backlight	LED
Power supply	DC 5V 2A

#### ST-300W-PB Player Box

Processor	Broadcom BCM2711, quad-core Cortex-A72
Memory	2GB LPDDR4
Video output	micro HDMI
Input power	DC 5V 3A
Mode Settings	Speaker / Audience
Connection	Wired & Wireless
Local Or Remote Mode Selection	Adjustable via 5" Podium Display

#### ST-300W-NP Timer Switcher

Input Voltage	5V DC
Max Current	1A
Connector	RJ45 8P8C socket
Total Ports	8 input/output ports
Max Total Cable Length	300 meters
Max Number of Devices	20 Devices (Excluding Splitters)
Recommended Cable Type	CAT5, CAT5E, CAT6
Local Or Remote Mode Selection	Adjustable via 5" Podium Display

#### Connections

Wireless Connection	802.11 LR - 2.4 ghz
Wireless Connection Range	100 Mt / 328 ft in clear field
Wired Connection	RS485 Communication
Wired Connection Range	500 Mt./ 1600 ft (Cat6 - Type B)
Wired Connection Jack	RJ-45

#### Mechanical Feature

Dimension LWH	400 x 580 x 230 mm
Weight	11 kg