

## **PARAPROJECT®**

## Trolley i32 PRO

charging, synchronizing, transport, storage, flex2connect





Part denomination	PARAPROJECT Trolley i32 PRO Charge&Sync, without cable
Part number	832.530-999
GTIN /EAN	4006793826991
Field of application	Education , Health Care
Certificates	CB / CE / GS
Applicable standards	DIN EN 55022 / DIN EN 55024 / DIN EN 61000-3-2 / DIN EN 61000-3-3 / DIN EN 60950-1
Scope of delivery	- 1x device connection cable EU, length 5 m
	- 1x USB cable, straight cable on both sides, length 1 m
	- 2x keys for separate pocket at the side
Materials	- ABS plastic
	- powder-coated steel sheet
Transport	4x wheels (Ø12 cm), with two lockable castors for safe handling / 2x carrying handles
External dimensions (WxDxH)	820 mm x 535 mm x 930 mm
Weight	72000 g
Transport dimensions	835 mm x 585 mm x 1100 mm
Dimensions of euro-plaletts	835 mm x 585 mm x 1100 mm
Number of euro-pallet	1
customs tariff number	94037000
Country of origin	TW
Fittings	- 2x 16 vertical pockets for one tablet each (with protective cover)
	- large drawer for master laptop and accessories
	- status display, 2x USB-B connection for sync function and 3 switchable sockets on top of the cart
	- master switch, power input, network connector, attachment hook and cable holder on the back of the cart
	- separate pocket at the side, lockable for e.g. access point
	- 2x retractable swing covers made from sheet steel, lockable with a standard padlock
	- media well for complete administration of the charge management at the back of the cart
	- constant running fan for optimum ventilation inside the cart
Compatible devices	all USB-chargeable tablets
Max. number of devices	32
Operating system	Android / iOS / Windows
Power supply	central power supply unit provides power for all devices
Output power per port	2,4 A
Optional accessories	- USB data and charging cable for all types
	- external weekly timer
Lock types	can be locked by a padlock



## **PARAPROJECT®**

## Trolley i32 PRO

 $charging\ ,\ synchronizing\ ,\ transport\ ,\ storage\ ,\ flex 2 connect$ 

Connections	- outside: - central power supply unit - master switch (on/off-switch) - network connector (RJ 45) - 2x USB 2.0 type B socket - 3x SCHUKO socket outlet with on/off-switch inside: - 2x 16 USB 2.0 type A socket- 1x patch cable with RJ 45 plug
Data of currents	- 100 - 240 V - max. 12 A - 50/60 Hz
Dimension of pockets	25 X 345 X 270
Domensions of other pockets	530 x 300 x 45
Color	white

product image similar / information without content / subject to errors and changes / all dimensions in mm





- 2x 16 USB 2.0 type A
- 1x patch cable with RJ 45 plug



- master switch (on/off-switch)
- network connector (RJ 45)
- 2x USB 2.0 type B socket
- 3x SCHUKO socket outlet with on /off-switch