



Malta - Interactive Touch Screen Kiosk

Transform your business, improve communications and operational efficiency.

Main features

- Free-standing design with option to bolt down base plate
- Power & data feed from rear panel or floor through the base plate
- Anti-Glare protection glass over the screen
- Key lockable access service door
- Ergonomic and compact structure
- User friendly, easy for maintenance



Touch technology - Capacitive
The Projective Capacitive (PCAP) touch technology with 12 touch points ensures a seamless and accurate touch response. With its AMVA3 LED panel, it offers exceptional colour performance, high contrast and wide viewing angles. This technology uses a sensor-grid of micro-fine wires integrated into the glass that covers the screen. Touch is detected because electrical characteristics of the sensor grid change when human finger is placed on the glass. Thanks to the glass overlay this technology is highly durable, and the touch function remains unaffected even if the glass is scratched. It offers perfect picture performance and will work with human finger (also latex gloved) and stylus-pen.



Smart Design
The sleek look is achieved with a striking aluminium surround and edge-to-edge vandal proof tempered glass front panel



Plug and Play
If there is no internet access available the screen can still be updated thanks to their backup USB update option.




24/7 Commercial Use
A commercial grade panel, with a lifespan of 50.000 hours and high quality components ensure that this display can be in constant use 24/7.



Technical Specifications

Screen	
Screen Size	32" K32ZE
Resolution	1920x1080
Brightness	450 cd/m2
Aspect Ratio	16:9
Contrast Ratio	5000:1
Viewing Angle	178:178
Response Time	8ms
Touch	
Touch Technology	PCAP - Projected Capacitive
Touch Points	Multi Touch
Response Time	8 ms
OS	Windows, Linux
Protection Glass	Tempered Anti Glare
Touch interface	USB
Touch method	finger
Other	
Application	Indoor
Colour	Black
Installation	Floor bolting / Free Standing
Enclosure	Metal
Working temperature	0°C~50°C
Power supply	AC 100-240V 50/60HZ



Dimension (mm)

Size	Model Name	A	B	C	D
32"	K32ZE	947	1170	641	80



Bravour Deutschland GmbH
 Alt-Heerdt 104
 40549 Düsseldorf - Germany
 Phone: (+49) 322 21093
 E-mail: info@bravour.com

Bravour Nederland BV
 De Rijn 7c
 5684 PJ Best - The Netherlands
 Phone: +31 (0) 40 2988 980
 E-mail: info@bravour.com

Bravour France SAS
 23, Rue de Richelieu
 75001 Paris - France
 Phone: +33 (0) 1 82 88 06 52
 E-mail: info@bravour.com