

2D LED Barcode Scanner User Manual





TABLE OF CONTENTS

COMPREHENSIVE SETTINGS	7
SETTING CODE	7
ENABLE AND DISABLE THE SETTING CODE	7
SENDING SETTING CODE	8
RESTORE FACTORY SETTINGS	8
VERSION NUMBER	8
USER DEFAULT SETTINGS	9
SOUND SETTINGS	10
ALL TONE SETTINGS	10
POWER-ON PROMT SOUND	10
SETTING CODE SOUND	10
PROMPT SOUND FOR SUCCESSFUL READING	10
SETTING SOUND VOLUME FOR SUCCESSFUL READING	11
SUCCESSFUL READING INDICATOR LIGHT	11
SETTING SUCCESSFUL READING INDICATOR LIGHT	11
DURATION OF THE INDICATOR LIGHT FOR READING BARCODE SUCCESSFUL	11
LIGHTING SETTINGS	12
FILL LIGHT ILLUMINATOR	12
AIMING LIGHT	12
MULTI-BYTE CHARACTER OUTPUT (OPTIONAL)	12
IMAGE RECOGNITION SETTINGS	13
IMAGE INVERSION (REVERSE WHITE) SETTING	13
NR IS PROMPTED IF THE BARCODE IS NOT SUCCESSFULLY READ	14
MODIFY NR INFORMATION	14
COMMUNICATION SETTINGS	15
INTRODUCTION	15
USB KEYBOARD INTERFACE	15
NATIONAL KEYBOARD LAYOUT	16
CASE CONVERSION	16
USB TRANSMISSION SPEED (DELAY BETWEEN CHARACTERS)	17
USB POLLING SPEED	18
USB-COM VIRTUAL SERIAL INTERFACE	18
USB HID-POS INTERFACE	19
TTL/RS232 SERIAL INTERFACE	20
BAUD RATE	20
PARITY TYPE	20
READING MODE	21
MANUAL READING MODE	21
MANUAL READING MODE-SINGLE READING TIME	21
MANUAL READING MODE-THE SAME BARCODE READING DELAY	21
CONTINUOUS READING MODE	23
CONTINUOUS READING MODE-SINGLE READING TIME	23
CONTINUOUS READING MODE-READING INTERVAL TIME	24
CONTINUOUS READING MODE-THE SAME BARCODE READING DELAY	24



INDUCTIVE / AUTO-SENSING READING MODE	26
INDUCTION MODE-SINGLE READING TIME LIMIT	26
INDUCTION READING MODE-SAME BARCODE READING DELAY	26
INDUCTION MODE-IMAGE STABILIZATION TIME	28
INDUCTION MODE-SENSITIVITY	28
DATA EDITING	29
INTRODUCTION	29
CODE ID SETTINGS	29
CODE ID PREFIX	29
CODE ID PREFIX	29
CUSTOM CODE ID	30
USER-DEFINED PREFIX	32
SEND USER-DEFINED PREFIX	32
USER-DEFINED PREFIX SETTING	32
USER-DEFINED SUFFIX	33
SEND USER-DEFINED SUFFIX	33
USER-DEFINED SUFFIX SETTING	33
HIDDEN CHARACTERS	34
STEP 1: SET THE FIELD LENGTH	34
STEP 2: SET THE TRANSMISSION FIELD	34
END CHARACTER SETTING	35
CUSTOM END SUFFIX	35
BARCODE PARAMETER SETTING	36
INTRODUCTION	36
GLOBAL SETTINGS	36
TURN ON/OFF ALL BARCODES	36
TURN ON/OFF 1D BARCODES	36
TURN ON/OFF 2D BARCODES	36
UPC-A	37
ALLOW/PROHIBIT READING UPC-A	37
SEND CHECK CHARACTER	37
TRANSMISSION SYSTEM CHARACTERS	37
2/5 ADDITIONAL BITS	38
CONVERT UPC-A TO EAN-13	38
UPC-E	39
ALLOW/PROHIBIT READING UPC-E0	39
SEND CHECK CHARACTER	39
TRANSMISSION SYSTEM CHARACTERS	39
ALLOW/PROHIBIT READING UPC-E1	39
SEND CHECK CHARACTER	40
TRANSMISSION SYSTEM CHARACTERS	40
2/5 ADDITIONAL BITS	40
EAN-8	41
ALLOW/PROHIBIT READING EAN-8	41
SEND CHECK CHARACTER	41
2/5 ADDITIONAL BITS	41



EAN-13	42
ALLOW/PROHIBIT READING EAN-13	42
SEND CHECK CHARACTER.....	42
2/5 ADDITIONAL BITS.....	42
CONVERT TO ISBN.....	43
CONVERT TO ISSN	43
CODE 128	43
ALLOW/PROHIBIT READING CODE 128	43
CODE 39	43
ALLOW/PROHIBIT READING CODE 39	43
CHECK CHARACTER SETTING	44
TRANSMIT START CHARACTER AND END CHARACTER.....	44
FULL ASCII RECOGNITION RANGE	44
CODE 32	45
ALLOW/PROHIBIT READING CODE 32	45
CODE 93	45
ALLOW/PROHIBIT READING CODE 93	45
CODABAR (NW-7)	45
ALLOW/PROHIBIT READING CODABAR	45
CHECK DIGIT SETTING	46
START CHARACTER AND STOP CHARACTER SETTING	46
INTERLEAVED 2 OF 5	47
ALLOW/PROHIBIT INTERLEAVED 2 OF 5.....	47
CHECK CHARACTER SETTING	47
MATRIX 2 OF 5	48
ALLOW/PROHIBIT MATRIX 2 OF 5	48
CHECK CHARACTER SETTING	48
INDUSTRIAL 2 OF 5	48
ALLOW/PROHIBIT INDUSTRIAL 2 OF 5	48
CHECK CHARACTER SETTING	48
STANDARD 2 OF 5 (IATA)	49
ALLOW/PROHIBIT STANDARD 2 OF 5	49
CHECK CHARACTER SETTING	49
CODE 11	49
ALLOW/PROHIBIT CODE 11	49
MSI PLESSEY	49
ALLOW/PROHIBIT MSI PLESSEY	49
QR CODE	50
ALLOW/PROHIBIT QR CODE	50
MICRO QR CODE	50
ALLOW/PROHIBIT MICRO QR CODE.....	50
DATA MATRIX	50
ALLOW/PROHIBIT DATA MATRIX	50
PDF 417	50
ALLOW/PROHIBIT PDF 417	50
GS1 DATABAR 14	51



GS1 DATABAR LIMITED	51
GS1 DATABAR EXPANDED	51
APPENDIX	52
APPENDIX-DATA CODE.....	52
APPENDIX-DATA CODE.....	52
APPENDIX-DATA CODE.....	53
APPENDIX-CODE ID	56
APPENDIX-ASCII CODE TABLE	56



COMPREHENSIVE SETTINGS

SETTING CODE

The scanner can set the function by reading the corresponding one or a group of special barcodes. In the following chapters, we will introduce the setting options and functions in detail and provide the corresponding setting codes.

INSTRUCTIONS

In manual barcode reading mode, the operation steps for scanning barcodes are as follows.

- 1 Press and hold the trigger button of the scanner. If aiming light is activated, and a red aiming line appears.
- 2 Aim the red line to the center of the barcode, move the scanner to adjust the distance between it and the barcode to find the best reading distance.
- 3 When you hear the success prompt sound and the aiming line goes out, the code reading is successful, and the scanner transmits the data after reading the code to the host.



During the reading process, for the same batch of barcodes, you will find that the distance between the scanner and the barcode is within a certain range, and the reading success rate will be very high. This distance is the best reading distance.

ENABLE AND DISABLE THE SETTING CODE

The setting code can be enabled or disabled. When the scanner is set to “Enable Setting Code” and you scan the setting code, the function will activate. However, when set to “Disable Setting Code”, scanning the setting code will trigger an error tone from the scan engine, rendering the setting function inactive.

By default, the setting is “*Enable Setting Code*”.



Enable Setting Code



Disable Setting Code



SENDING SETTING CODE

The content of the setting code can be allowed to be sent. After reading the “send setting code” and setting successfully, the content will be sent to the host when the setting code is read; after reading the “do not send setting code” and setting is successful, the scanner will no longer send the setting code content.

By default, the setting is “*Do Not Send Setting Code*”



Send Setting Code



Do Not Send Setting Code

RESTORE FACTORY SETTINGS

All scanners have a factory default setting. Reading the “*Restore Factory Settings*” barcode will make all the scanner’s properties setting software default state.



Restore Factory Settings

INSTRUCTIONS

You are most likely to use this barcode in the following situations:

- 1 The scanner settings are incorrect, such as the barcode cannot be recognized.
- 2 You forgot what settings you made to the scanner before, and you don’t want to use the previous settings.
- 3 Set the scanner to use some infrequently used functions, and use it after completion.

VERSION NUMBER

Use the scanner to scan the version number barcode, you can view the current scanner version number information,



Show Version Number



USER DEFAULT SETTINGS

In addition to the factory settings, users can also save their frequently used configuration as user default settings. By scanning "***Save User Default Settings***", the current configuration information of the device can be saved as user default settings. If there are already users Default setting information in the module, the new configuration information after this operation will replace the original user default setting information.



Save User Default Settings



Recover User Default Settings

EXAMPLE

Set the closed EAN-13 code as a user default setting:

- 1 Scan the barcode of "***Enable Setting Code***";
- 2 Scan the barcode "***EAN-13 is prohibited***";
- 3 Scan the barcode of "***Save User Default Settings***";
- 4 Scan the barcode of "***Disable Setting Code***".



SOUND SETTINGS

ALL TONE SETTINGS



Turn on all sounds



Turn off all sounds

POWER-ON PROMPT SOUND

Turn on or turn off the beep sound when starting up.



Turn on sound



Turn off sound

SETTING CODE SOUND

Scan setting code prompt sound on or off.



Turn on the setting code sound



Turn off the setting code sound

PROMPT SOUND FOR SUCCESSFUL READING

Set the prompt sound on or off after reading code successfully.



Turn on sound for successful reading



Turn off sound for successful reading



SETTING SOUND VOLUME FOR SUCCESSFUL READING

Set the volume of the prompt sound for reading barcode successfully.



Low sound volume for
successful reading



Middle sound volume for
successful reading



High sound volume for
successful reading

SUCCESSFUL READING INDICATOR LIGHT

SETTING SUCCESSFUL READING INDICATOR LIGHT



Turn on successful reading indicator



Turn off successful reading indicator

DURATION OF THE INDICATOR LIGHT FOR READING BARCODE SUCCESSFUL

Read the following setting codes, you can modify the LED prompt time.

By default, the setting is "200 ms".

MODIFY THE LED PROMPT TIME TO:



100ms



200ms



500ms



prompt time

EXAMPLE

Customize and modify the LED prompt time to 300ms, you can set it according to the following steps:

- 1 Scan the "**Enable setting code**" (you don't need to scan when it is turned on);
- 2 Scan the setting code of "**Customize and Modify LED Prompt Time**";
- 3 Scan the "**3**", "**0**" and "**0**" setting codes in turn in **Appendix-Data Code**;
- 4 Scan the "**Save**" or "**Cancel**" setting code in **Appendix-Save**;
- 5 Scan the "**Disable Settings code**".



LIGHTING SETTINGS

FILL LIGHT ILLUMINATOR

The illuminator can provide auxiliary lighting for shooting and reading, and the light beam illuminates the reading target to improve the reading performance and the ability to adapt to weak ambient light. The user can set it to one of the following states according to the application environment:

ELEMENT	ACTION
Turn on (default)	The illuminator lights up during shooting and reading, and goes out at other times.
Always on	The lighting lamp will continue to glow after the engine is turned on.
Turn off	The illuminator will not light up under any circumstances.



Turn on



Always on



Turn off

AIMING LIGHT

The aiming beam can help users find the best reading distance when shooting and reading. Users can choose any of the following modes according to the application environment.

By default, The aiming light is turned on during shooting and scanning.

ELEMENT	ACTION
Turn on (default)	The aiming light flashes during shooting and reading, and turn off at other times.
Always on	After the reading engine is powered on, the aiming beam is continuously reading
Turn off	the aiming light will not light up under any circumstances.



Turn on



Always on



Turn off

MULTI-BYTE CHARACTER OUTPUT (OPTIONAL)



Japanese (For TXT)



Japanese (For Word)



Traditional Chinese (For TXT)



IMAGE RECOGNITION SETTINGS

IMAGE INVERSION (REVERSE WHITE) SETTING

Normal phase bar code: bar code with light background and dark bar

Inverted bar code: dark background, light bar code, also known as reverse white bar code, reverse color bar code

ALLOW READING:



Reverse color barcode



1D reverse color barcodes



Reverse color QR Code



Data Matrix reverse color code



PDF 417 reverse color code

PROHIBIT READING:



Reverse color barcode



1D reverse color barcodes



Reverse color code of QR Code



Data Matrix reverse color



PDF 417 reverse color code



NR IS PROMPTED IF THE BARCODE IS NOT SUCCESSFULLY READ

Before releasing the trigger button, if the barcode cannot be read within the timeout period, it is allowed to send NR (No Read) message. Any feasible prefix or suffix can be attached to this message

ELEMENT	ACTION
Turn on	When the code reading is unsuccessful, the button will be released or the code reading timeout will send the unsuccessful code reading message (the default value is empty).
Turn off	When the code reading is unsuccessful, the message of unsuccessful code reading will not be sent.



Turn on



Turn off

MODIFY NR INFORMATION

Read the following setting codes, and you will start to change the NR information. This setting code needs to be combined and configured with the data code. If you directly read the **"Save"** of the data code, the length of the NR message will be "zero". In this case, even if the NR message is required to be sent, there will be no substantial information content. The output may cause confusion to the performance in use, please set it carefully.

The length of the NR information that can be set is 0~7 characters, and the character value range is 0~255.



Modify NR information

EXAMPLE

Modify the NR information to the string **"!ERR"**.

- 1 Check the character table to get the hexadecimal value corresponding to **"!ERR"**: **21, 45, 52, 52**;
- 2 Read the **"Enable Setting Code"**; (If it is already enabled, you can skip this step);
- 3 Read **"Modify NR Information"**;
- 4 Read the data code **"2", "1", "4", "5", "5", "2", "5", "2"**;
- 5 Read the data code **"Save"**;
- 6 Read the **"Disable Setting Code"**.



COMMUNICATION SETTINGS

INTRODUCTION

When using this scanner to communicate with different hosts, you need to set the scanner to the corresponding communication interface mode. You can set the scanner's functions by scanning one or more setting bar codes. You can choose to use USB (USB-KBW, USB-COM), TTL, RS232 serial communication interface modes, etc.

USB KEYBOARD INTERFACE

The USB keyboard interface is the USB-KBW interface. When the USB data line is connected, the scanner can be set to the USB-KBW input mode. In this mode, the scanner will become a virtual keyboard, and the data receiving host accepts the virtual keyboard input like a real keyboard input. The sending process after the scanner reads the code and obtains the data is to hit each key corresponding to the data in the virtual keyboard.

The default scanner uses USB-KBW communication, simulating USB keyboard input mode, no driver installation is required.



USB-KBW interface



NATIONAL KEYBOARD LAYOUT

The keyboard key arrangement, symbols, etc. corresponding to different national languages are not the same. The scanner can be virtualized into different national keyboard standards according to actual needs. The keyboard layout setting is applicable to the USB-KBW interface mode, and the default is “*American English keyboard*”.



US/China English
(American English)



Germany (German)



United Kingdom
(British English)



Spain (Spanish)



France (French)



Italy (Italian)



Portugal (Portuguese)



Brazil (Portuguese)



Belgium (Dutch)



Turkish-Q

CASE CONVERSION



Normal**



Upper



Lower



Inverse



USB TRANSMISSION SPEED (DELAY BETWEEN CHARACTERS)

This parameter is used to adjust the delay time between scanner barcode characters. When the input host needs slower data transmission, scan the corresponding barcode below to increase the inter-character delay, which can adjust the transmission speed and improve the safety and integrity of output data.

Keyboard output character interval, range 0-75ms, default: **2ms**



Default delay



No delay



Short delay



Long delay



Custom delay

EXAMPLE

To set the delay between characters to 15ms, you can set it according to the following steps:

- 1 Scan the **"Enable Setting code"**;
- 2 Scan the **"Custom Delay"** setting code;
- 3 Scan the **"1"** and **"5"** setting codes in **Appendix-Data Code**;
- 4 Scan the **"Save"** setting code in **Appendix-Save and Cancel Settings**;
- 5 Scan the **"Disable Settings code"**.



USB POLLING SPEED

The keyboard polling speed can be set to 1~10 ms by the following setting code. The smaller the set value, the faster the reading module can send characters to the host. If the host will lose characters, please increase the polling speed setting value.

POLLING SPEED:



1 ms



2 ms



3 ms



4 ms



5 ms



6 ms



7 ms



8 ms



9 ms



0 ms

USB-COM VIRTUAL SERIAL INTERFACE

When the scanner uses a USB connection, and at the same time you want the host to receive data through a serial port, you should use the USB virtual serial port. From the point of view of the host system interface, the scanner is equivalent to connecting with the host through a serial port. This function requires the corresponding driver to be installed on the host.



USB-COM



USB HID-POS INTERFACE

The USB HID-POS interface is recommended for new application software. Based on the HID interface, no driver is required.



USB HID-POS

PROTOCOL FORMAT:

VID	PID
0x26f1	0x8803

HOST SEND DATA FORMAT

BYTE	CONTENT
0	Message ID (0x04)
1	Effective data length
2-61	data
62	0x00, 1 byte reserved
63	0x00 (no data behind) 0x01 (data behind)

DATA FORMAT SENT BY SCANNING DEVICE TO HOST

BYTE	CONTENT
0	Message ID (0x02)
1	Effective data length
2-61	data
62	0x00, 5 byte reserved
63	0x00 (no data behind) 0x01 (data behind)



TTL/RS232 SERIAL INTERFACE

Serial communication interface is a common way to connect scanners and host devices, and can be used to connect to host devices such as PCs and POS machines. When the scanner uses the serial communication interface, the scanner and the host device must match the serial communication protocol parameter configuration completely to ensure the accuracy of the transmitted data.



TTL/RS232

PARAMETER	DEFAULT
Serial communication type	Standard TTL/RS232
Baud Rate	9600
Parity Type	None
Data Bits	8
Stop Bits	1

BAUD RATE

The baud rate is the number of bits transmitted per second in serial data communication. The baud rate used by the scanner and the data receiving host must be consistent to ensure the accuracy of data transmission. The scanner supports the baud rates listed below in bit/s.



1200bps



2400bps



4800bps



9600bps*



19200bps



38400bps



57600bps



115200bps

PARITY TYPE



Odd parity ODD



Even parity EVEN



NONE



READING MODE

MANUAL READING MODE

Set to manual reading mode, press the button to start reading, and the reading will not stop when the button is released, the reading will stop if the reading is successful or the reading exceeds the single reading time.



Manual reading mode

MANUAL READING MODE-SINGLE READING TIME

In the trigger mode, the longest shooting and reading time is allowed when the trigger level is maintained. After this time limit, no matter whether the reading is successful or not, the shooting and reading action will be stopped. The setting range of the single reading time is 1000~3600000ms, and the default time is 3000ms.

QUICK SETTING OF SINGLE READING TIME



Single reading time 3000ms



Single reading time 5000ms



Customize and modify the single reading time

EXAMPLE

To set the limit time of a single code reading to 1500ms, you can set it according to the following steps:

- 1 Scan the **"Enable Setting code"**;
- 2 Scan the setting code of **"Customize and modify single reading time"**;
- 3 Scan the **"1", "5", "0"** and **"0"** setting codes in **Appendix-Data Code** in turn;
- 4 Scan the **"Save"** setting code in **Appendix-Save and Cancel Settings**;
- 5 Scan the **"Disable Settings code"**.

MANUAL READING MODE-THE SAME BARCODE READING DELAY

In order to avoid the same barcode being read multiple times in a short time in the trigger mode, you can request the reading module to delay the set time in this mode before allowing the same barcode to be read.

The same barcode reading delay means that after reading a barcode, within the set time, refuse to read the same barcode. Only after the duration has expired can it be read and output.

Set to **"Reading the same barcode without delay"**, the same barcode will be output immediately after reading.

Set to **"Require the same bar code reading delay"** and set **"Reread timeout without reset"**, which means that



the same bar code can be read and transmitted after the timeout limit time after reading the same bar code.

Set to **"Require the same barcode reading delay"** and set **"Reread timeout reset"**, which means that the same barcode will not be read and transmitted if it continues to read the same barcode within the limited time after reading.

If the same barcode delay is set to **"Modify the same barcode reading delay is unlimited"**, the same barcode will not be read repeatedly and will not be output without power failure.



No delay when reading
the same barcode



Require the same
barcode reading delay



Reread timeout
does not reset



Reread timeout reset

Read the following setting codes, you can quickly modify the limit value of the same code reading delay time. The same code reading delay setting range is 0~65535ms, and the default duration is 1500ms. Custom modify the same code reading delay time



When modifying the same code
reading delay is unlimited



Modify the same code
reading delay 1000ms



Modify the same code
reading delay 1500ms



Modify the same code
reading delay 3000ms



Modify the same code
reading delay 5000ms



Custom modify the same
code reading delay time

EXAMPLE

Set custom and modify the same code reading delay time to 8000ms.

- 1 Scan the **"Enable Setting code"** setting code;
- 2 Scan the setting code of **"Customize and modify single reading time"**;
- 3 Scan the **"8"**, **"0"**, **"0"** and **"0"** setting codes in **Appendix-Data Code** in turn;
- 4 Scan the **"Save"** setting code in **Appendix-Save and Cancel Settings**;
- 5 Scan the **"Disable Settings code"** setting code.



CONTINUOUS READING MODE

After setting, the scanner is in continuous scanning state, without triggering, the reading engine starts to read the code immediately. When the reading is successful, the information is output or the single reading time is over, the reading engine will wait for a period of time (settable) and it will start automatically Read the code once. If the following conditions do not occur, the scanning engine will work in cycles as described above: the user can also click the trigger button to manually pause the code reading during the code reading process. Click the trigger button to read the engine and continue to read the code cyclically.



Continuous reading mode

CONTINUOUS READING MODE-SINGLE READING TIME

In the continuous mode, it refers to the maximum duration of continuous acquisition and recognition before the reading is successful. After the timeout, it will enter the interval of no acquisition and reading according to the setting. The setting range of the single reading time is 1000~3600000ms, and the default time is 3000ms.

QUICK SETTING OF SINGLE READING TIME



Single reading time 3000ms



Single reading time 5000ms



Customize and modify the single reading time

EXAMPLE

To set the limit time of a single code reading to 1500ms, you can set it according to the following steps:

- 1 Scan the **"Enable Setting"** setting code (you don't need to scan when it is turned on);
- 2 Scan the setting code of **"Customize and modify single reading time"**;
- 3 Scan the **"1", "5", "0"** and **"0"** setting codes in **Appendix-Data Code**;
- 4 Scan the **"Save"** setting code in **Appendix-Save and Cancel Settings**;
- 5 Scan the **"Disable Settings"** setting code.



CONTINUOUS READING MODE-READING INTERVAL TIME

The reading interval is the time between two readings. Regardless of whether the reading is successful or unsuccessful, there will be a set time interval between two readings, during which no acquisition and reading will be performed. The setting range of the reading interval is 0~65535ms, the default time is 1000ms



Modify the reading interval to 500ms



Modify the reading interval to 1000ms



Modify the reading interval to 2000ms



Modify the reading interval to 5000ms



Modify the reading interval to 0ms



Customize and modify the reading interval

To set the reading interval to 800ms, you can set it according to the following steps:

- 1 Scan the **"Enable Setting"** setting code (you don't need to scan when it is turned on);
- 2 Scan the setting code of **"Customize and modify the reading interval"**;
- 3 Scan the **"8"**, **"0"** and **"0"** setting codes in **Appendix-Data Code**;
- 4 Scan the **"Save"** setting code in **Appendix-Save and Cancel Settings**;
- 5 Scan the **"Disable Settings"** setting code.

CONTINUOUS READING MODE-THE SAME BARCODE READING DELAY

In order to avoid the same bar code being read multiple times in a short period of time in the continuous reading mode, you can request the reading module to delay the set time in this mode before allowing the same bar code to be read.

The same barcode reading delay means that after reading a barcode, within the set time, refuse to read the same barcode. Only after the duration has expired can it be read and output.

Set to **"Reading the same barcode without delay"**, the same barcode will be output immediately after reading.

Set to **"Require the same bar code reading delay"** and set **"Reread timeout without reset"**, which means that the same bar code can be read and transmitted after the timeout limit time after reading the same bar code.

Set to **"Require the same barcode reading delay"** and set **"Reread timeout reset"**, which means that the same barcode will not be read and transmitted if it continues to read the same barcode within the limited time after reading.

If the same barcode delay is set to **"Modify the same barcode reading delay is unlimited"**, the same barcode will not be read repeatedly and will not be output without power failure.



No delay when reading
the same barcode



Require the same
barcode reading delay



Reread timeout
does not reset



Reread timeout reset

Read the following setting codes, you can quickly modify the limit value of the same code reading delay time. The same code reading delay setting range is 0~65535ms, and the default duration is 1500ms. Custom modify the same code reading delay time



When modifying the same code
reading delay is unlimited



Modify the same code
reading delay 1000ms



Modify the same code
reading delay 1500ms



Modify the same code
reading delay 3000ms



Modify the same code
reading delay 5000ms



Custom modify the same
code reading delay time

EXAMPLE

Set custom modification of the same code reading delay time to 8000ms.

- 1 Scan the "**Enable Setting**" setting code (you don't need to scan when it is turned on);
- 2 Scan the setting code of "**Customize and modify single reading time**";
- 3 Scan the "**8**", "**0**", "**0**" and "**0**" setting codes in **Appendix-Data Code**;
- 4 Scan the "**Save**" setting code in **Appendix-Save and Cancel Settings**;
- 5 Scan the "**Disable Settings**" setting code.



INDUCTIVE / AUTO-SENSING READING MODE

In the auto-sensing mode, the reading module will monitor the captured images. When the scene changes, it will be read within the "single reading time" within a limited time. After the reading is successful, it will output information or time out, and then re-enter the monitoring The state of the scene change.

When the reading module works in this mode, it can also respond to the trigger level and enter the reading state. After the trigger level is cancelled, the reading is successful, or the timeout, it will re-enter the state of monitoring scene changes. Before entering the monitoring state again, the trigger level needs to be cancelled.



Auto-sensing mode

INDUCTION MODE-SINGLE READING TIME LIMIT

Single reading time limit: it is the longest time allowed to maintain the shooting and reading attempt after the scene change is monitored and the reading state is entered, and the reading is not successful. When this time is exceeded, the reading state will return to the monitoring state. The setting range of the single reading time is 1000~3600000ms, and the default time is 3000ms.



Modify the single reading time 3000ms



Modify the single reading time 5000ms



Custom modify the limit of single reading time

EXAMPLE

To set the limit time of a single code reading to 1500ms, you can set it according to the following steps:

- 1 Scan the "**Enable Setting**" setting code;
- 2 Scan the setting code of "**Custom modify single reading time limit**";
- 3 Scan the "**1**", "**5**", "**0**" and "**0**" setting codes in **Appendix-Data Code**;
- 4 Scan the "**Save**" setting code in **Appendix-Save and Cancel Settings**;
- 5 Scan the "**Disable Settings**" setting code.

INDUCTION READING MODE-SAME BARCODE READING DELAY

In order to avoid the same bar code being read multiple times in a short period of time in the induction reading mode, the reading module can be required to read the same bar code after a delay in this mode.

The same barcode reading delay means that after reading a barcode, within the set time, refuse to read the same barcode. Only after the duration has expired can it be read and output.

Set to "**Reading the same barcode without delay**", the same barcode will be output immediately after reading.



Set to ***“Require the same bar code reading delay”*** and set ***“Reread timeout without reset”***, which means that the same bar code can be read and transmitted after the timeout limit time after reading the same bar code.

Set to ***“Require the same barcode reading delay”*** and set ***“Reread timeout reset”***, which means that the same barcode will not be read and transmitted if it continues to read the same barcode within the limited time after reading.

If the same barcode delay is set to ***“Modify the same barcode reading delay is unlimited”***, the same barcode will not be read repeatedly and will not be output without power failure.



No delay when reading the same barcode



Require the same barcode reading delay



Reread timeout does not reset



Reread timeout reset

Read the following setting codes, you can quickly modify the limit value of the same code reading delay time. The same code reading delay setting range is 0~65535ms, and the default duration is 1500ms. Custom modify the same code reading delay time



When modifying the same code reading delay is unlimited



Modify the same code reading delay 1500ms



Modify the same code reading delay 5000ms



Modify the same code reading delay 1000ms



Modify the same code reading delay 3000ms



Custom modify the same code reading delay time

EXAMPLE

Set custom modification of the same code reading delay time to 8000ms.

- 1 Scan the ***“Enable Setting”*** setting code;
- 2 Scan the setting code of ***“Customize and modify single reading time”***;
- 3 Scan the ***“8”***, ***“0”***, ***“0”*** and ***“0”*** setting codes in **Appendix-Data Code**;
- 4 Scan the ***“Save”*** setting code in **Appendix-Save and Cancel Settings**;
- 5 Scan the ***“Disable Settings”*** setting code.



INDUCTION MODE-IMAGE STABILIZATION TIME

In the induction mode, when the scanner stops reading the code, it will enter a process of re-adapting to the changes in the reading environment (image). After the image is stabilized, it will enter the induction state and wait for the barcode to appear. By modifying the image stabilization timeout, the time to adapt to the environment can be adjusted. The setting range of image stabilization time is 0~1600ms, and the default image stabilization time is 60ms.



The image stabilization time is 60ms



Image stabilization time 500ms



Image stabilization time 1000ms



Modify the image stabilization time

EXAMPLE

Set the image stabilization time to 500ms

- 1 Scan the "**Enable Setting**" setting code;
- 2 Scan the "**Modify image stabilization time**" setting code;
- 3 Scan the "**5**", "**0**" and "**0**" setting codes in **Appendix-Data Code**;
- 4 Scan the "**Save**" setting code in **Appendix-Save and Cancel Settings**;
- 5 Scan the "**Disable Settings**" setting code.

INDUCTION MODE-SENSITIVITY

Sensitivity refers to the degree of change in the detection scene in the induction reading mode. When the reading module judges that the degree of scene change meets the requirements, it will switch from the monitoring state to the reading state.



Very high sensitivity



High sensitivity



Medium sensitivity



Low sensitivity



DATA EDITING

INTRODUCTION

After the scanner successfully reads the code, the device obtains a string of data, which can be numbers, English, symbols, etc. In practical applications, we may not only need the data information of the bar code, or the data information contained in the bar code cannot meet your needs. For example, you may want to know which type of bar code this string of data information comes from, or attach special data to this string of data, which may not be included in the data information of the bar code.

Adding these content when making codes will inevitably increase the length of the bar code and is not flexible enough, which is not a recommended practice. At this time, we thought of artificially adding some content before or after the barcode data information, and these added content can be changed in real time according to needs, and you can choose to add or block. This is the prefix and suffix of the barcode data information. , Which not only satisfies the demand but does not need to modify the content of the barcode information.



DATA EDITING FORMAT:

<Code ID><custom prefix><barcode data><custom suffix><terminator>

CODE ID SETTINGS

CODE ID PREFIX

In the process of using a scanner, you often need to know the type of barcode currently scanned. We can use the Code ID prefix to identify the barcode type. Please refer to **Appendix-Code ID** for the corresponding barcode type of Code ID.

The default is "*Close Code ID*".



Turn on Code ID



Turn off Code ID



Restore all barcode Code ID default values

CODE ID PREFIX



Code ID + custom prefix



Custom prefix + Code ID



CUSTOM CODE ID

The Code ID corresponding to each barcode type can be modified freely. The Code ID of all barcodes is 1 character and must be a letter, and cannot be set as a number, invisible character, or punctuation, etc.

The Code ID of each barcode type can be modified independently, it needs to be used by reading the corresponding setting code and combining with the data code.



Modify PDF417 Code ID



Modify Code128 Code ID



Modify QR Code ID



Modify DM Code ID



Modify EAN8 Code ID



Modify EAN13 Code ID



Modify UPCE0 Code ID



Modify UPCE1 Code ID



Modify UPCA Code ID



Modify IATA25 Code ID



Modify Code 39 Code ID



Modify Code 93 Code ID

Modify Interleaved
2 of 5 Code ID

Modify Codabar Code ID

Modify Industrial
25 Code ID

Modify Matrix 25 Code ID



Modify Code 11 Code ID

Modify MSI Plessey
Code ID

Modify Micro QR Code ID



Modify Code32 Code ID



Modify ISBN Code ID



Modify ISSN Code ID

Modify GS1 DataBar
Code IDModify GS1 DataBar
Limited Code ID

Modify GS1 DataBar Expanded Code ID

EXAMPLE

Modify PDF417 Code ID to the letter 'p'

- 1 Look up the table and get the hexadecimal value corresponding to "*p*" is *70*;
- 2 Scan the "**Enable Setting**" setting code;
- 3 Scan the "**Modify PDF417 Code ID**" setting code;
- 4 Scan the "*7*" and "*0*" setting codes in **Appendix-Data Code** in turn;
- 5 Scan the "**Save**" setting code in **Appendix-Save and Cancel Settings**;
- 6 Scan the "**Disable Settings**" setting code.



USER-DEFINED PREFIX

SEND USER-DEFINED PREFIX

If the user has set a custom prefix, the scanner needs to be set to transmit the custom prefix to transmit the user-defined prefix information. The default is *"Do not transmit custom prefixes"*.



Send user-defined prefix



Do not transmit user-defined prefixes

USER-DEFINED PREFIX SETTING

Users can set custom prefixes for different barcode types according to the **Appendix-Code ID** information. Add up to 10 characters for the custom prefix.



Set custom prefix

EXAMPLE

Add a custom prefix of XYZ to all barcode types

First, query the HEX value corresponding to XYZ as **58,59,5A**.

- 1 Scan the **"Enable Settings"** setting code;
- 2 Scan the **"Set custom prefix"** setting code;
- 3 Scan **"5", "8", "5", "9", "5",** and **"A"** in **Appendix-Data Code**.
- 4 Scan the **"Save"** setting code in **Appendix-Save or Cancel**.
- 5 Scan the **"Transfer Custom Prefix"** setting code to complete the configuration.



USER-DEFINED SUFFIX

SEND USER-DEFINED SUFFIX

If the user has set a custom suffix, the scanner needs to be set to transmit the custom suffix to transmit the user-defined suffix information. The default is *"Do not transmit custom suffixes"*.



Send user-defined suffix



Do not transmit user-defined suffixes

USER-DEFINED SUFFIX SETTING

Users can set custom suffixes for different barcode types according to the **Appendix-Code ID** information. Add up to 10 characters for the custom suffix.



Set custom suffix

EXAMPLE

Add a custom suffix of XYZ to all barcode types

First, the HEX corresponding to XYZ is only **58,59,5A** by querying.

- 1 Scan the **"Enable Settings"** setting code;
- 2 Scan the **"Custom Suffix"** setting code;
- 3 Scan **"5", "8", "5", "9", "5",** and **"A"** in **Appendix-Data Code** in turn.
- 4 Scan the **"Save"** setting code in **Appendix-Save or Cancel**.
- 5 Scan the **"Transfer custom suffix"** setting code to complete the configuration.



HIDDEN CHARACTERS

STEP 1: SET THE FIELD LENGTH



Send user-defined suffix



Do not transmit user-defined suffixes



The length of the field is in bytes (1 byte for English characters and 2 bytes for Chinese characters), using hexadecimal data for configuration. The length modification range is 0-255.

EXAMPLE

Set the length of the Start field to 4 (hexadecimal 0x04) and the length of the End field to 12 (hexadecimal 0x0C).

- 1 Scan the "**Startup Settings**" setting code;
- 2 Scan the "**Set Start field length**" setting code;
- 3 Scan the number "0", "4" of **Appendix-Data Code** to set the code;
- 4 Scan the "**Save**" setting code of **Appendix-Save and Cancel Settings**.
- 5 Scan the "**Set End Field Length**" setting code;
- 6 Scan the number "0", "C" setting code in **Appendix-Data Code**;
- 7 Scan the "**Save**" setting code of **Appendix-Save and Cancel Settings**.

STEP 2: SET THE TRANSMISSION FIELD



Transfer complete
Data field



Only the Start field
is transmitted



Only transfer the
Center field



Only the End field
is transmitted

EXAMPLE

After setting the complete Data barcode "12345678901234567890", the length of the Start field is 4 and the length of the End field is 12:

- 1 Set "**Transfer Complete Data Field**" and the output result is: **12345678901234567890**
- 2 Set "**only transfer Start field**" output result is: **1234**
- 3 Set "**only transfer Center field**" output result is: **5678**
- 4 Set "**Transfer End Field Only**" and the output result is: **901234567890**



END CHARACTER SETTING

The terminator suffix is used to mark the end of a complete data message. The terminator suffix must be the last content when a piece of data is sent, and there will be no additional data after that.



Allow ending character



No terminator is allowed



Add CR



Add CR+LF

CUSTOM END SUFFIX

Read the “modify end character” and combine to read the data code to modify the character content of the end character.

When modifying end character, use 2 hexadecimal values to represent the characters, and read 2 or 4 values sequentially to represent 1 character or 2 characters. For the hexadecimal conversion of characters, please refer to “**Appendix-ASCII Code Table**”.



Modify end character

EXAMPLE

Modify the ending character to the letter 0x0D

- 1 Scan the “**Start Setting**” setting code;
- 2 Scan the “**Modify end character**” setting code;
- 3 Scan the “**0**” and “**D**” setting codes in **Appendix-Data Code**;
- 4 Scan the “**Save**” setting code in **Appendix-Save and Cancel Settings**;
- 5 Scan the “**Close Settings**” setting code.



BARCODE PARAMETER SETTING

INTRODUCTION

Each type of barcode has its own unique attributes, and the scanner can be adjusted to adapt to these attribute changes through the setting codes in this chapter. The fewer barcode types that enable “*Allow Reading*”, the faster the scanning speed of the scanner. You can prevent the scanner from reading unused barcode types to improve the scanner’s working performance.

GLOBAL SETTINGS

TURN ON/OFF ALL BARCODES



Turn on all barcodes



Turn off all barcodes

TURN ON/OFF 1D BARCODES



Turn on 1D barcodes



Turn off 1D barcodes

TURN ON/OFF 2D BARCODES



Turn on 2D barcodes



Turn off 2D barcodes



UPC-A

ALLOW/PROHIBIT READING UPC-A



Allow reading UPC-A



Prohibit reading UPC-A

SEND CHECK CHARACTER

The UPC-A barcode data is fixed to 12 characters, and the 12th digit is the check character, which is used to verify the correctness of all 12 characters. The default is to transmit the check character.



Send check character



Do not transmit check characters

TRANSMISSION SYSTEM CHARACTERS

The first digit of UPC-A barcode is a system character, and its value is fixed as "0"



Transmission system characters



Do not transmit system characters



2/5 ADDITIONAL BITS

Additional digits refer to the 2 or 5 digital barcodes appended to the normal barcode, as shown in the figure below. The blue line frame on the left is the normal barcode, and the red line frame on the right is the additional digit. The default is to turn off the extra bit.



Turn on 2 additional bits



Turn on 5 additional bits



Turn off 2 additional bits



Turn off 5 additional bits

CONVERT UPC-A TO EAN-13



Barcode information conversion



Barcode information is not converted



UPC-E

ALLOW/PROHIBIT READING UPC-E0



Allow reading UPC-E0



Prohibit reading UPC-E0

SEND CHECK CHARACTER

UPC-E0 barcode data is fixed to 8 characters, the 8th digit is a check character, used to verify the correctness of all 8 characters, the default is to transmit a check character.



Send check character



Do not transmit check characters

TRANSMISSION SYSTEM CHARACTERS



Transmission system characters



Do not transmit system characters

ALLOW/PROHIBIT READING UPC-E1



Allow reading UPC-E1



Prohibit reading UPC-E1



SEND CHECK CHARACTER

UPC-E1 barcode data is fixed to 8 characters, and the 8th digit is a check character, which is used to verify the correctness of all 8 characters. The default is to transmit a check character.



Send check character



Do not transmit check characters

TRANSMISSION SYSTEM CHARACTERS



Transmission system characters



Do not transmit system characters

2/5 ADDITIONAL BITS

Additional digits refer to the 2 or 5 digital barcodes appended to the normal barcode, as shown in the figure below. The blue line frame on the left is the normal barcode, and the red line frame on the right is the additional digit. The default is to turn off the extra bit.



Open 2 additional bits



Open 5 additional bit code



Turn off 2 additional bits



Turn off 5 additional bits



EAN-8

ALLOW/PROHIBIT READING EAN-8



Allow reading EAN-8



Prohibit reading EAN-8

SEND CHECK CHARACTER

The EAN-8 barcode data is fixed to 8 characters, and the 8th digit is the check character, which is used to verify the correctness of all 8 characters. The default is to transmit the check character.



Send check character



Do not transmit check characters

2/5 ADDITIONAL BITS

Additional digits refer to the 2 or 5 digital barcodes appended to the normal barcode, as shown in the figure below. The blue line frame on the left is the normal barcode, and the red line frame on the right is the additional digit. The default is to turn off the extra bit.



Turn on 2 additional bits



Turn on 5 additional bits



Turn off 2 additional bits



Turn off 5 additional bits



EAN-13

ALLOW/PROHIBIT READING EAN-13



Allow reading EAN-13



Prohibit reading EAN-13

SEND CHECK CHARACTER

The EAN-13 barcode data is fixed to 13 characters, and the 13th digit is the check character, which is used to verify the correctness of all 13 characters. The default is to transmit the check character.



Send check character



Do not transmit check characters

2/5 ADDITIONAL BITS

Additional digits refer to the 2 or 5 digital barcodes appended to the normal barcode, as shown in the figure below. The blue line frame on the left is the normal barcode, and the red line frame on the right is the additional digit. The default is to turn off the extra bit.



Turn on 2 additional bits



Turn on 5 additional bits



Turn off 2 additional bits



Turn off 5 additional bits



CONVERT TO ISBN



Barcode information conversion



Barcode information is not converted

CONVERT TO ISSN



Barcode information conversion



Barcode information is not converted

CODE 128

ALLOW/PROHIBIT READING CODE 128



Allow reading Code 128



Prohibit reading Code 128

CODE 39

ALLOW/PROHIBIT READING CODE 39



Allow reading Code 39



Prohibit reading Code 39



CHECK CHARACTER SETTING

Code 39 barcode data is not mandatory to include a check character. If there is a check character, it is the last character of the data. The check character is a value calculated based on all data to check whether the data is correct. You can turn on or off the check according to your needs, and set whether to send check characters.



Check and send verification



Verify but do not
transmit verification



Do not send verification

TRANSMIT START CHARACTER AND END CHARACTER

Code 39 barcode data has a character "*" before and after it is used as the start character and stop character. You can set whether to transmit the start character and stop character together with the barcode data after the barcode is successfully read.



Transmit start character and end character



Do not transmit start and end characters

FULL ASCII RECOGNITION RANGE

Code 39 code data can include all ASCII characters, but the scanner only reads part of ASCII characters by default. By setting, you can turn on the function of reading complete ASCII characters

The default is *"Do not recognize full ASCII characters"*



Recognize full ASCII characters



Does not recognize full ASCII characters



CODE 32

ALLOW/PROHIBIT READING CODE 32

Code 32, Code 32 Pharmaceutical, is a form of Code 39 barcode used by Italian pharmacies. This bar code is also called PARAF.

The output format of Code 32 is: The output format is: * + A + 8 digits + 1 digit check + *.



Allow reading Code 32



Prohibit reading Code 32



Code 32 is converted from Code39 to Code32. When Code32 is turned on, Code 39 will be affected. It can be read only when Code39 is enabled and without verification, and Code 32 can be read without verification. .

CODE 93

ALLOW/PROHIBIT READING CODE 93



Allow reading Code 93



Prohibit reading Code 93

CODABAR (NW-7)

ALLOW/PROHIBIT READING CODABAR



Allow reading Codabar



Prohibit reading Codabar



CHECK DIGIT SETTING



Modulo 10 verification and transmission verification



Modulo 16 verification and transmission verification



Modulo 10 verification and no verification



Modulo 16 verification and no verification



No verification

START CHARACTER AND STOP CHARACTER SETTING

Codabar start and end characters are allowed to be one of the four characters "A", "B", "C", and "D"; the terminator is also allowed to be "T", "N", "*", "E" one of these four characters. The start and end characters are not transmitted by default



Start and end characters
ABCD/ABCD



Start and end ABCD/TN*E



Start and end abcd/abcd



Start and end abcd/tn*e



Do not transmit start and end characters



INTERLEAVED 2 OF 5

ALLOW/PROHIBIT INTERLEAVED 2 OF 5



Allow to read Interleaved 2 of 5*



Prohibit reading Interleaved 2 of 5

CHECK CHARACTER SETTING

Interleaved 2 of 5 barcode data is not mandatory to include a check character. If there is a check character, it is the last character of the data. The check character is a value calculated based on all data to check whether the data is correct. You can turn on or off the check according to your needs, and set whether to send check characters.

The code digits of Interleaved 2 of 5 barcodes must be even, the check character is included in the code, if it is odd, the first digit must be 0. Check character Check character is a code



USS verification and
transmission verification



USS verification does not
transmit verification



No verification



MATRIX 2 OF 5

ALLOW/PROHIBIT MATRIX 2 OF 5



Allow to read Matrix 2 of 5



Prohibit reading Matrix 2 of 5*

CHECK CHARACTER SETTING

Matrix 2 of 5 barcode data is not mandatory to include a check character. If there is a check character, it must be the last byte of the data. The check character is a value calculated from all data except the check character to verify whether the data is correct.



Check and send verification



Verify but do not
transmit verification



No verification

INDUSTRIAL 2 OF 5

ALLOW/PROHIBIT INDUSTRIAL 2 OF 5



Allow to read Industrial 2 of 5



Prohibit reading Industrial 2 of 5

CHECK CHARACTER SETTING

Industrial 2 of 5 barcode data does not compulsorily include a check character. If there is a check character, it must be the last byte of the data. The check character is a value calculated from all data except the check character, used to check whether the data is correct.



Check and send verification



Verify but do not
transmit verification



No verification*



STANDARD 2 OF 5 (IATA)

ALLOW/PROHIBIT STANDARD 2 OF 5



Allow to read Standard 2 of 5



Prohibit reading Standard 2 of 5

CHECK CHARACTER SETTING

Standard 2 of 5 barcode data is not mandatory to include a check character. If there is a check character, it must be the last byte of the data. The check character is a value calculated from all data except the check character, used to check whether the data is correct.



Check and send verification



Verify but do not
transmit verification



No verification

CODE 11

ALLOW/PROHIBIT CODE 11



Allow to read Code 11



Prohibit reading Code 11

MSI PLESSEY

ALLOW/PROHIBIT MSI PLESSEY



Allow to read MSI Plessey



Prohibit reading MSI Plessey



QR CODE

ALLOW/PROHIBIT QR CODE



Allow to read QR Code



Prohibit reading QR Code

MICRO QR CODE

ALLOW/PROHIBIT MICRO QR CODE



Allow to read Micro QR Code



Prohibit reading Micro QR Code

DATA MATRIX

ALLOW/PROHIBIT DATA MATRIX



Allow to read Data Matrix



Prohibit reading Data Matrix

PDF 417

ALLOW/PROHIBIT PDF 417



Allow to read PDF 417



Prohibit reading PDF 417



GS1 DATABAR 14



**Allow to read GS1 DataBar 14



Prohibit reading GS1 DataBar 14

GS1 DATABAR LIMITED



**Allow to read GS1 DataBar Limited



Prohibit reading RSS-Limited

GS1 DATABAR EXPANDED



**Allow to read GS1 DataBar Expanded



Prohibit reading RSS-Expanded



APPENDIX

APPENDIX-DATA CODE



0



1



2



3



4



5



6



7



8



9



A



B



C



D



E



F

APPENDIX-DATA CODE

After reading the data code, you must read the save code to save the read data. If an error occurs when reading the data code, you can cancel reading the wrong data in addition to resetting.

For example, read a certain setting code and read the data "1", "2", and "3" in turn. At this time, if you read "cancel the previous data read", the last read number "3" will be cancelled. If you read "Cancel a string of data previously read", the read data "123" will be canceled; if you read "Cancel current setting", it will cancel the setting code together.



Save Settings

Cancel the previous
data readCancel a string of data
previously read

Cancel current setting



APPENDIX-DATA CODE

SETTINGS	PARAMETER	DEFAULT SETTING	REMARK
COMPREHENSIVE SETTINGS	Setting code function	ON	
	Send setting code	OFF	
	All tones	ON	
	Power-on prompt	ON	
	Setup code prompt tone	ON	
	Prompt for successful reading	ON	
	Volume of prompt tone for successful barcode reading	high	
	Reading success indicator light	ON	
	Duration of the indicator light for successful barcode reading	ON	200ms
	Fill light	ON	
	Aiming light	ON	
	Aiming light flashes	ON	
	Data input format	Auto	
	Data output format	GBK	
	Invoice function	OFF	
	Image inversion	OFF	
	Prompt for unsuccessful reading	OFF	
COMMUNICATION SETTINGS	Interface mode	USB-KBW	
	Inter-character delay	2MS	
	USB polling speed	1MS	
	Keyboard mode	American English	
	Control character escape	OFF	
	Baud rate	9600	
	Serial verification	No verification	
	Data bit	8	
	Stop bit	1	
READING MODE	Reading mode	Manual reading	
	Manual reading mode-single reading time	3S	
	Manual reading mode-the same barcode reading delay	No delay	
	Continuous reading mode-single reading time	3S	
	Continuous reading mode-reading interval time	1000MS	
	Continuous reading mode-the same barcode reading delay	No delay	
	Induction reading mode-single reading time	3S	
	Induction reading mode-image stabilization time	60MS	
	Induction reading mode-induction sensitivity	High sensitivity	



SETTINGS	PARAMETER	DEFAULT SETTING	REMARK
DATA EDITING	Send Code ID	OFF	
	Code ID prefix	Code ID + Custom prefix	
	Send custom prefix	OFF	
	Send custom suffix	OFF	
	Hide header data	OFF	
	Hide central data	OFF	
	Hide tail data	OFF	
	Allow terminator	ON	
	Terminator	ON	CR
BARCODE PARAMETER SETTING	Turn on all barcodes	OFF	
	Turn on all 1D barcodes	OFF	
	Turn on all QR codes	OFF	
UPC-A	Allow reading	ON	
	Send check character	ON	
	Transmission system characters	ON	
	Read 2 additional bits	OFF	
	Read 5 additional bits	OFF	
	Convert to EAN-13	OFF	
UPC-E	Allow reading UPC-E0	ON	
	UPC-E0 transmission system character	ON	
	Allow reading UPC-E1	ON	
	Send check character	ON	
	UPC-E1 transmission system characters	ON	
	Read 2 additional bits	OFF	
	Read 5 additional bits	OFF	
	Mandatory additional bits, 2 bits allowed	OFF	
	Mandatory additional bits, 5 bits allowed	OFF	
EAN-8	Allow reading	ON	
	Send check character	ON	
	Read 2 additional bits	OFF	
	Read 5 additional bits	OFF	
EAN-13	Allow reading	ON	
	Send check character	ON	
	Read 2 additional bits	OFF	
	Read 5 additional bits	OFF	
	Convert to ISBN	OFF	
	Convert to ISSN	OFF	
CODE 128	Allow reading	ON	



SETTINGS	PARAMETER	DEFAULT SETTING	REMARK
CODE 39	Allow reading	ON	
	Turn on verification	OFF	
	Transmission check	OFF	
	Transmission start character and end character	OFF	
	Recognize Full ASCII	OFF	
CODE 32	Allow reading	OFF	
CODE 93	Allow reading	OFF	
	Turn on verification	OFF	
	Transmission check	OFF	
CODABAR	Allow reading	ON	
	Turn on verification	OFF	
	Transmission check	OFF	
	Transmission start character and end character	OFF	
	Start and stop format	ABCD/ABCD	
INTERLEAVED 2 OF 5	Allow reading	ON	
	Turn on verification	OFF	
	Transmission check	OFF	
MATRIX 2 OF 5	Allow reading	OFF	
	Turn on verification	OFF	
	Transmission check	OFF	
INDUSTRIAL 2 OF 5	Allow reading	OFF	
	Turn on verification	OFF	
	Transmission check	OFF	
STANDARD 2 OF 5	Allow reading	OFF	
	Turn on verification	OFF	
	Transmission check	OFF	
CODE 11	Allow reading	OFF	
MSI PLESSEY	Allow reading	OFF	
QR CODE	Allow reading	ON	
MICRO QR CODE	Allow reading	ON	
DATA MATRIX	Allow reading	ON	
PDF 417	Allow reading	ON	
GS1 DATABAR14	Allow reading	ON	
GS1 DATABAR LIMITED	Allow reading	ON	
GS1 DATABAR EXPANDED	Allow reading	ON	



APPENDIX-CODE ID

NO.	BARCODE TYPE	CODE ID
1	UPC-A, UPC-E	c
2	EAN-8, EAN-13, ISBN, ISSN	d
3	CODE 39, Code 32	b
4	Codabar	a
5	Code 128	j
6	Code 93	i
7	Interleaved 2 of 5	e
8	Matrix 2 of 5	v
9	Industrial 2 of 5	D
10	Standard 2 of 5 (IATA25)	s
11	PDF 417	r
12	DataMatrix	u
13	QR Code, Micro QR	Q
14	Code 11	H
15	MSI Plessey	J
16	GS1 DataBar	R
17	GS1 DataBar Limited	R
18	GS1 DataBar Expanded	R

APPENDIX-ASCII CODE TABLE



ASCII code table 0-31 are invisible characters used as control characters, and 32-127 are visible characters

HEXADECIMAL	ASCII VALUE (DECIMAL)	CHARACTER
00	00	NUL (Null char.)
01	01	SOH (Start of Header)
02	02	STX (Start of Text)
03	03	ETX (End of Text)
04	04	EOT (End of Transmission)
05	05	ENQ (Enquiry)
06	06	ACK (Acknowledgment)
07	07	BEL (Bell)
08	08	BS (Backspace)
09	09	HT (Horizontal Tab)
0A	10	LF (Line Feed)
0B	11	VT (Vertical Tab)
0C	12	FF (Form Feed)
0D	13	CR (Carriage Return)



HEXADECIMAL	ASCII VALUE (DECIMAL)	CHARACTER
0E	14	SO (Shift Out)
0F	15	SI (Shift In)
10	16	DLE (Data Link Escape)
11	17	DC1 (XON) (Device Control 1)
12	18	DC2 (Device Control 2)
13	19	DC3 (XOFF) (Device Control 3)
14	20	DC4 (Device Control 4)
15	21	NAK (Negative Acknowledgment)
16	22	SYN (Synchronous Idle)
17	23	ETB (End of Trans. Block)
18	24	CAN (Cancel)
19	25	EM (End of Medium)
1A	26	SUB (Substitute)
1B	27	ESC (Escape)
1C	28	FS (File Separator)
1D	29	GS (Group Separator)
1E	30	RS (Request to Send)
1F	31	US (Unit Separator)
20	32	SP (Space)
21	33	! (Exclamation Mark)
22	34	" (Double Quote)
23	35	# (Number Sign)
24	36	\$ (Dollar Sign)
25	37	% (Percent)
26	38	& (Ampersand)
27	39	` (Single Quote)
28	40	((Right / Closing Parenthesis)
29	41	) (Right / Closing Parenthesis)
2A	42	* (Asterisk)
2B	43	+ (Plus)
2C	44	, (Comma)
2D	45	- (Minus / Dash)
2E	46	. (Dot)
2F	47	/ (Forward Slash)
30	48	0
31	49	1
32	50	2
33	51	3
34	52	4



HEXADECIMAL	ASCII VALUE (DECIMAL)	CHARACTER
35	53	5
36	54	6
37	55	7
38	56	8
39	57	9
3A	58	: (Colon)
3B	59	; (Semi-colon)
3C	60	< (Less Than)
3D	61	= (Equal Sign)
3E	62	> (Greater Than)
3F	63	? (Question Mark)
40	64	@ (AT Symbol)
41	65	A
42	66	B
43	67	C
44	68	D
45	69	E
46	70	F
47	71	G
48	72	H
49	73	I
4A	74	J
4B	75	K
4C	76	L
4D	77	M
4E	78	N
4F	79	O
50	80	P
51	81	Q
52	82	R
53	83	S
54	84	T
55	85	U
56	86	V
57	87	W
58	88	X
59	89	Y
5A	90	Z
5B	91	[(Left / Opening Bracket)



HEXADECIMAL	ASCII VALUE (DECIMAL)	CHARACTER
5C	92	\ (Back Slash)
5D	93	] (Right / Closing Bracket)
5E	94	^ (Caret / Circumflex)
5F	95	_ (Underscore)
60	96	' (Grave Accent)
61	97	a
62	98	b
63	99	c
64	100	d
65	101	e
66	102	f
67	103	g
68	104	h
69	105	i
6A	106	j
6B	107	k
6C	108	l
6D	109	m
6E	110	n
6F	111	o
70	112	p
71	113	q
72	114	r
73	115	s
74	116	t
75	117	u
76	118	v
77	119	w
78	120	x
79	121	y
7A	122	z
7B	123	{ (Left/ Opening Brace)
7C	124	(Vertical Bar)
7D	125	} (Right/Closing Brace)
7E	126	~ (Tilde)
7F	127	DEL (Delete)







WASTE ELECTRICAL & ELECTRONIC EQUIPMENT DISPOSAL OF ELECTRIC AND ELECTRONIC EQUIPMENT

(Applicable In The European Union And Other European Countries With Separate Collection Systems)



ENGLISH: This symbol on the product or its packaging means that this product must not be treated as unsorted household waste. In accordance with EU Directive 2012/19/EU on Waste Electrical and Electronic Equipment (WEEE),

this electrical product must be disposed of in accordance with the user's local regulations for electrical or electronic waste.

Please dispose of this product by returning it to your local point of sale or recycling pickup point in your municipality.

DEUTSCH: Dieses auf dem Produkt oder der Verpackung angebrachte Symbol zeigt an, dass dieses Produkt nicht mit dem Hausmüll entsorgt werden darf. In Übereinstimmung mit der Richtlinie 2012/19/EU des Europäischen Parlaments und des Rates über Elektro- und Elektronik-Altgeräte (WEEE) darf dieses Elektrogerät nicht im normalen Hausmüll oder dem Gelben Sack entsorgt werden. Wenn Sie dieses Produkt entsorgen möchten, bringen Sie es bitte zur Verkaufsstelle zurück oder zum Recycling-Sammelpunkt Ihrer Gemeinde.

ESPAÑOL: Este símbolo en el producto o su embalaje indica que el producto no debe tratarse como residuo doméstico. De conformidad con la Directiva 2012/19/EU de la UE sobre residuos de aparatos eléctricos y electrónicos (RAEE), este producto eléctrico no puede desecharse se con el resto de residuos no clasificados. Deshágase de este producto devolviéndolo a su punto de venta o a un punto de recolección municipal para su reciclaje.

FRANÇAIS: Ce symbole sur le produit ou son emballage signifie que ce produit ne doit pas être traité comme un déchet ménager. Conformément à la Directive 2012/19/EU sur les déchets d'équipements électriques et électroniques (DEEE), ce produit électrique ne doit en aucun cas être mis au rebut sous forme de déchet municipal non trié. Veuillez vous débarrasser de ce produit en le renvoyant à son point de vente ou au point de ramassage local dans votre municipalité, à des fins de recyclage.

ITALIANO: Questo simbolo sul prodotto o sulla relativa confezione indica che il prodotto non va trattato come un rifiuto domestico. In ottemperanza alla Direttiva UE 2012/19/EU sui rifiuti di apparecchiature elettriche ed elettroniche (RAEE), questa prodotto elettrico non deve essere smaltito come rifiuto municipale misto. Si prega di smaltire il prodotto riportandolo al punto vendita o al punto di raccolta municipale locale per un opportuno riciclaggio.

POLSKI: Jeśli na produkcie lub jego opakowaniu umieszczono ten symbol, wówczas w czasie utylizacji nie wolno wyrzucać tego produktu wraz z odpadami komunalnymi. Zgodnie z Dyrektywą Nr 2012/19/EU w sprawie zużytego sprzętu elektrycznego i elektronicznego (WEEE), niniejszego produktu elektrycznego nie wolno usuwać jako nie posortowanego odpadu komunalnego. Prosimy o usunięcie niniejszego produktu poprzez jego zwrot do punktu zakupu lub oddanie do miejscowego komunalnego punktu zbiórki odpadów przeznaczonych do recyklingu.

WARRANTY INFORMATION • GARANTIEINFORMATIONEN • GARANTÍA • GARANTIE • GWARANCJI • GARANZIA

manhattanproducts.com

EN MÉXICO: Póliza de Garantía Intellinet Network Solutions — Datos del importador y responsable ante el consumidor IC Intracom México, S.A.P.I. de C.V. • Av. Interceptor Poniente # 73, Col. Parque Industrial La Joya, Cuautitlán Izcalli, Estado de México, C.P. 54730, México. • Tel. (55)1500-4500 La presente garantía cubre los siguientes productos contra cualquier defecto de fabricación en sus materiales y mano de obra.

A. Garantizamos los productos de limpieza, aire comprimido y consumibles, por 60 días a partir de la fecha de entrega, o por el tiempo en que se agote totalmente su contenido por su propia función de uso, lo que suceda primero.

B. Garantizamos los productos con partes móviles por 3 años.

C. Garantizamos los demás productos por 5 años (productos sin partes móviles), bajo las siguientes condiciones:

1. Todos los productos a que se refiere esta garantía, ampara su cambio físico, sin ningún cargo para el consumidor.
2. El comercializador no tiene talleres de servicio, debido a que los productos que se garantizan no cuentan con reparaciones, ni refacciones, ya que su garantía es de cambio físico.
3. La garantía cubre exclusivamente aquellas partes, equipos o sub-ensambles que hayan sido instaladas de fábrica y no incluye en ningún caso el equipo adicional o cualesquiera que hayan sido adicionados al mismo por el usuario o distribuidor.

Para hacer efectiva esta garantía bastará con presentar el producto al distribuidor en el domicilio donde fue adquirido o en el domicilio de IC Intracom México, S.A.P.I. de C.V., junto con los accesorios contenidos en su empaque, acompañado de su póliza debidamente llenada y sellada por la casa vendedora (indispensable el sello y fecha de compra) donde lo adquirió, o bien, la factura o ticket de compra original donde se mencione claramente el modelo, número de serie (cuando aplique) y fecha de adquisición. Esta garantía no es válida en los siguientes casos: Si el producto se hubiese utilizado en condiciones distintas a las normales; si el producto no ha sido operado conforme a los instructivos de uso; o si el producto ha sido alterado o tratado de ser reparado por el consumidor o terceras personas.



REGULATORY STATEMENTS

FCC Class B

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of Federal Communications Commission (FCC) Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy, and if not installed and used in accordance with the instructions may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures: reorient or relocate the receiving antenna; increase the separation between the equipment and the receiver; connect the equipment to an outlet on a circuit different from the receiver; or consult the dealer or an experienced radio/TV technician for help.

CE

ENGLISH: This device complies with the requirements of CE 2014/30/EU and/or 2014/35/EU. The Declaration of Conformity for is available at:

DEUTSCH: Dieses Gerät entspricht der CE 2014/30/EU und / oder 2014/35/EU. Die Konformitätserklärung für dieses Produkt finden Sie unter:

ESPAÑOL: Este dispositivo cumple con los requerimientos de CE 2014/30/EU y / o 2014/35/EU. La declaración de conformidad esta disponible en:

FRANÇAIS: Cet appareil satisfait aux exigences de CE 2014/30/EU et / ou 2014/35/EU. La Déclaration de Conformité est disponible à:

POLSKI: Urządzenie spełnia wymagania CE 2014/30/EU i / lub 2014/35/EU. Deklaracja zgodności dostępna jest na stronie internetowej producenta:

ITALIANO: Questo dispositivo è conforme alla CE 2014/30/EU e / o 2014/35/EU. La dichiarazione di conformità è disponibile al:

support.manhattanproducts.com/barcode/153997



North America

IC Intracom America
550 Commerce Blvd.
Oldsmar, FL 34677 USA

Asia & Africa

IC Intracom Asia
4-F, No. 77, Sec. 1, Xintai 5th Rd.
Xizhi Dist., New Taipei City 221, Taiwan

Europe

IC Intracom Europe
Löhbacher Str. 7, D-58553
Halver, Germany

All trademarks and trade names are the property of their respective owners.

Alle Marken und Markennamen sind Eigentum Ihrer jeweiligen Inhaber.

Todas las marcas y nombres comerciales son propiedad de sus respectivos dueños.

Toutes les marques et noms commerciaux sont la propriété de leurs propriétaires respectifs.

Wszystkie znaki towarowe i nazwy handlowe należą do ich właścicieli.

Tutti i marchi registrati e le denominazioni commerciali sono di proprietà dei loro rispettivi proprietari.